



The fraction of light intensity reflected and transmitted (refracted) from an air-glass interface at normal ( $\theta = 0^\circ$ ) incidence is

- A)  $\frac{I_{refl}}{I_0} = \left(\frac{2n_1}{n_2 + n_1}\right)^2$  and  $\frac{I_{trans}}{I_0} = \left(\frac{2n_2}{n_2 + n_1}\right)^2$ .
- B)  $\frac{I_{refl}}{I_0} = \left(\frac{2n_1}{n_2 + n_1}\right)^2$  and  $\frac{I_{trans}}{I_0} = \left(\frac{n_2 - n_1}{n_2 + n_1}\right)^2$ .
- C)  $\frac{I_{refl}}{I_0} = \left(\frac{n_2 - n_1}{n_2 + n_1}\right)^2$  and  $\frac{I_{trans}}{I_0} = \left(\frac{2n_1}{n_2 + n_1}\right)^2$ .

The amplitudes are  $A_{trans} = \frac{2 \sin \theta_2 \cos \theta_1}{\sin(\theta_1 + \theta_2)} A_0$  and  $A_{refl} = -\frac{\sin(\theta_1 - \theta_2)}{\sin(\theta_1 + \theta_2)} A_0$ .

When  $\theta_1 = \theta_2 = 0^\circ$ , using  $\cos 0^\circ = 1$  and  $\frac{\sin \theta_1}{\sin \theta_2} = \frac{n_2}{n_1}$ , we have  $A_{trans} =$

$\frac{2n_1}{n_1 + n_2} A_0$  and  $A_{refl} = \frac{n_2 - n_1}{n_1 + n_2} A_0$ . Light intensity is proportional to the

square of the amplitude,  $\frac{I_{refl}}{I_0} = \left(\frac{n_2 - n_1}{n_1 + n_2}\right)^2$  and  $\frac{I_{trans}}{I_0} = \left(\frac{2n_1}{n_1 + n_2}\right)^2$ .

Answer C.